

Packings

Type No.	Category	Application
Type 6711 	Expanded graphite packing	Valve packing for Power plants Recommended for high pressure and high temperature valves Temp : -200~600 C Pressure : ANSI Class 1500
Type EDP15 	Expanded graphite packing	Valve packing for Refinery, Chemical & Petro-chemical Plants Emission defence Packing Temp : -200~400 C Pressure : ASME Class 900 2200 psi (155 bar)
Type 6521L 	Carbonized fiber packing	Pump, mixers packing Temperature: 200°C, Pressure: 1.2MPa Application: Sea water pump
Type 4536WL 	Aramid fiber packing	Shaft packing for low speed Application: Paper making plant, chemical plant

Gaskets

Type No.	Category	Application
Type 5600 	Aramid fiber hybrid rubber sheet	For Flange, Lining Pipe, Sea Water Intake Pipe Temperature: -30~120 °C, Pressure: 2.6 MPa
Type 6633 	Expanded graphite sheet gasket	For Flange, Power Plant Temperature: -200~400°C, Pressure: 5.2MPa Application: Flanges for pipe, Equipment
Type 4001/4002/4003 	PTFE Gasket Pillar	For Flange, Food / Chem Industry Temperature: -210~260°C, Pressure: 4001 & 4003: 8.3MPa, 4002: 5.1 Application No.4001- Low creep and excellent acid resistance No.4002-High compression characteristics No.4003-Excellent alkali resistance
Type 2303-EEE 	Gasket Pillar	For Flange, Food / Chem Industry Application: for filler material, and the SUS304 is used for hoop and inner race/outer race Performance Temperature: -200°C - +260°C Pressure: Water base fluid:34.3MPa, Gas base fluid:15.5MPa
Type 2603-EEE 	Gasket Pillar	For Flange, Power Plant Temperature: -200°C - +600°C (450°C for oxidizing atmosphere) Pressure: 43.1MPa Application: for wide range of fluid

A Division of :



UP-TOWN INDUSTRIAL SALES, INC.





Up-Town Bldg., 56-58 Madison St., Mandaluyong City, Philippines

Tel No. : 631-8366 to 75 loc. 112

Fax No. : 631-5290 / 631-5296

Website : www.uptown.com.ph

Mechanical Seals

Type No.	Category	Application
Type JAB 	Stationary Floating Ring Seal (Heavy duty)	For high load application (Boiler feed pump) Performance Pressure : 10 Mpa Velocity : 80 m/s Dia : 50-250
Type GAKEM 	Cartridge Type Mechanical Seal Pillar Casette Seal (R)	Applicable to wide range of fluids Performance Pressure : 1 Mpa Velocity : 2000mPa/s
Type AAB 	Rotating Multi-spring Seal	For general application Performance Pressure : 3.43 Mpa Velocity : 20 m/s Dia : 20-250
Type GAKEM 	Welded Metal Bellow Seal	Application : Oil feed pump Fuel Transfer Pump Performance Pressure : 3 Mpa Velocity : 60 mPa/s Dia. : 23-136

A Division of :



UP-TOWN INDUSTRIAL SALES, INC.

Up-Town Bldg., 56-58 Madison St., Mandaluyong City, Philippines

Tel No. : 631-8366 to 75 loc. 112

Fax No. : 631-5290 / 631-5296

Website : www.uptown.com.ph